

Axima EWK R0

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	16	16	16	16	16	18	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
EWK-15-680/05 in m3/h	13.2	18.5	21.4	11.1	17.6	15.0	21.2	24.5	12.7	20.2	17.2	24.3	28.1	14.6	23.3	19.0	26.8	30.9	16.1	25.6	21.9	31.0	35.8	18.6	29.7
EWK-20-680/08 in m3/h	26.3	37.1	42.8	22.2	35.3	30.0	42.4	48.9	25.4	40.4	34.5	48.7	56.2	29.2	46.5	37.9	53.5	61.9	32.1	51.2	43.9	62.0	71.6	37.3	59.4
EWK-30-1260/05 in m3/h	39.5	55.6	64.2	33.3	52.9	45.1	63.6	73.4	38.1	60.6	51.7	73.0	84.4	43.8	69.8	56.9	80.3	92.8	48.2	76.8	65.8	92.9	107.5	55.9	89.1
EWK-35-1260/05 in m3/h	52.7	74.2	85.6	44.4	70.5	60.1	84.7	97.9	50.8	80.8	69.0	97.3	112.5	58.4	93.0	75.9	107.1	123.7	64.3	102.4	87.8	123.9	143.3	74.5	118.8
EWK-40-1260/08 in m3/h	65.8	92.7	107.0	55.6	88.1	75.1	105.9	122.4	63.5	101.0	86.2	121.7	140.6	73.0	116.3	94.8	133.8	154.7	80.4	128.0	109.7	154.9	179.1	93.1	148.5
EWK-50-1800/05 in m3/h	79.0	111.2	128.4	66.7	105.8	90.1	127.1	146.8	76.2	121.2	103.5	146.0	168.7	87.6	139.5	113.8	160.6	185.6	96.4	153.7	131.6	185.9	214.9	111.8	178.2
EWK-60-1800/05 in m3/h	92.1	129.8	149.8	77.8	123.4	105.2	148.3	171.3	88.9	141.4	120.7	170.3	196.9	102.2	162.8	132.7	187.4	216.6	112.5	179.3	153.6	216.9	250.7	130.4	207.9
EWK-60-1800/08 in m3/h	105.3	148.3	171.2	88.9	141.0	120.2	169.5	195.8	101.6	161.6	138.0	194.7	225.0	116.8	186.0	151.7	214.1	247.5	128.6	204.9	175.5	247.9	286.6	149.0	237.6
EWK-65-2100/05 in m3/h	118.5	166.9	192.6	100.0	158.7	135.2	190.7	220.2	114.3	181.8	155.2	219.0	253.1	131.4	209.3	170.7	240.9	278.4	144.7	230.5	197.5	278.8	322.4	167.6	267.3
EWK-70-2100/05 in m3/h	131.6	185.4	214.0	111.1	176.3	150.2	211.8	244.7	127.0	202.0	172.5	243.4	281.2	146.0	232.5	189.6	267.7	309.4	160.7	256.1	219.4	309.8	358.2	186.3	297.0
EWK-70-2100/08 in m3/h	144.8	203.9	235.4	122.2	193.9	165.3	233.0	269.2	139.7	222.2	189.7	267.7	309.4	160.6	255.8	208.6	294.4	340.3	176.8	281.7	241.3	340.8	394.0	204.9	326.7
EWK-75-3100/05 in m3/h	158.0	222.5	256.8	133.3	211.5	180.3	254.2	293.7	152.4	242.4	207.0	292.0	337.5	175.2	279.0	227.6	321.2	371.2	192.9	307.3	263.3	371.8	429.8	223.5	356.4
EWK-80-3100/08 in m3/h	184.3	259.6	299.6	155.6	246.8	210.3	296.6	342.6	177.8	282.7	241.5	340.7	393.7	204.4	325.5	265.5	374.7	433.1	225.0	358.5	307.2	433.7	501.5	260.8	415.9
EWK-80-4500/08 in m3/h	210.6	296.7	342.4	177.8	282.1	240.4	339.0	391.5	203.2	323.1	275.9	389.4	450.0	233.6	372.0	303.4	428.3	495.0	257.2	409.7	351.0	495.7	573.1	298.0	475.3
EWK-80-5100/05 in m3/h	237.3	334.3	385.8	200.3	317.8	270.9	381.9	441.2	229.0	364.1	310.9	438.7	507.0	263.3	419.2	341.9	482.6	557.8	289.8	461.7	395.6	558.6	645.8	335.8	535.5

Axima EWK R0

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
EWK-15-680/05 in m3/h	25.5	36.0	41.6	21.7	34.6	29.7	42.0	48.6	25.3	40.4	33.0	46.6	53.9	28.1	44.9	39.1	55.2	63.9	33.4	53.4	35.1	28.2	40.2	35
EWK-20-680/08 in m3/h	51.0	72.0	83.3	43.3	69.2	59.4	84.0	97.1	50.6	80.8	66.0	93.2	107.8	56.3	89.8	78.2	110.5	127.8	66.8	106.7	70.2	56.4	80.4	70
EWK-30-1260/05 in m3/h	76.5	108.0	124.9	65.0	103.8	89.2	126.0	145.7	75.9	121.2	99.0	139.8	161.7	84.4	134.8	117.3	165.7	191.7	100.2	160.1	105.3	84.6	120.6	105
EWK-35-1260/05 in m3/h	102.0	144.0	166.5	86.7	138.3	118.9	167.9	194.2	101.2	161.7	132.0	186.4	215.6	112.5	179.7	156.5	221.0	255.6	133.6	213.4	140.4	112.8	160.7	140
EWK-40-1260/08 in m3/h	127.4	180.0	208.2	108.4	172.9	148.6	209.9	242.8	126.6	202.1	165.0	233.0	269.5	140.6	224.6	195.6	276.2	319.5	167.0	266.8	175.5	141.0	200.9	175
EWK-50-1800/05 in m3/h	152.9	216.0	249.8	130.0	207.5	178.3	251.9	291.4	151.9	242.5	198.0	279.6	323.4	168.8	269.5	234.7	331.4	383.4	200.4	320.2	210.6	169.2	241.1	210
EWK-60-1800/05 in m3/h	178.4	252.0	291.4	151.7	242.1	208.1	293.9	339.9	177.2	282.9	231.0	326.2	377.3	196.9	314.4	273.8	386.7	447.4	233.8	373.5	245.7	197.4	281.3	245
EWK-60-1800/08 in m3/h	203.9	288.0	333.1	173.4	276.7	237.8	335.9	388.5	202.5	323.3	264.0	372.8	431.3	225.0	359.3	312.9	441.9	511.3	267.2	426.9	280.8	225.6	321.5	280
EWK-65-2100/05 in m3/h	229.4	324.0	374.7	195.0	311.3	267.5	377.9	437.1	227.8	363.7	297.0	419.4	485.2	253.2	404.3	352.0	497.2	575.2	300.6	480.2	315.9	253.8	361.7	315
EWK-70-2100/05 in m3/h	254.9	360.0	416.3	216.7	345.9	297.2	419.8	485.6	253.1	404.1	329.9	466.0	539.1	281.3	449.2	391.1	552.4	639.1	334.0	533.6	351.0	282.0	401.8	350
EWK-70-2100/08 in m3/h	280.4	396.0	458.0	238.4	380.4	327.0	461.8	534.2	278.4	444.5	362.9	512.6	593.0	309.4	494.1	430.3	607.6	703.0	367.5	587.0	386.1	310.2	442.0	385
EWK-75-3100/05 in m3/h	305.9	432.0	499.6	260.1	415.0	356.7	503.8	582.7	303.7	485.0	395.9	559.2	646.9	337.5	539.0	469.4	662.9	766.9	400.9	640.3	421.2	338.4	482.2	420
EWK-80-3100/08 in m3/h	356.8	504.0	582.9	303.4	484.2	416.1	587.8	679.9	354.4	565.8	461.9	652.4	754.7	393.8	628.8	547.6	773.4	894.7	467.7	747.0	491.4	394.8	562.6	490
EWK-80-4500/08 in m3/h	407.8	576.0	666.1	346.7	553.4	475.6	671.7	777.0	405.0	646.6	527.9	745.6	862.5	450.1	718.7	625.8	883.8	1022.5	534.5	853.8	561.6	451.2	642.9	560
EWK-80-5100/05 in m3/h	459.5	649.0	750.6	390.7	623.5	535.9	756.9	875.5	456.3	728.6	594.8	840.2	971.9	507.1	809.8	705.2	995.9	1152.2	602.2	962.0	632.8	508.4	724.5	631