

Ryoden RT-U, R1, 2016

| Condition Reference # | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Wet Bulb °C | 10 | 10 | 10 | 10 | 10 | 13 | 13 | 13 | 13 | 13 | 16 | 16 | 16 | 16 | 16 | 18 | 18 | 18 | 18 | 18 | 21 | 21 | 21 | 21 | 21 |
| Range °C | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 |
| Approach °C | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 |
| Inlet Water Temperature °C | 20 | 22 | 23 | 22 | 25 | 23 | 25 | 26 | 25 | 28 | 26 | 28 | 29 | 28 | 31 | 28 | 30 | 31 | 30 | 33 | 31 | 33 | 34 | 33 | 36 |
| Outlet Water Temperature °C | 14 | 16 | 17 | 14 | 17 | 17 | 19 | 20 | 17 | 20 | 20 | 22 | 23 | 20 | 23 | 22 | 24 | 25 | 22 | 25 | 25 | 27 | 28 | 25 | 28 |
| RT-80U/SB in m3/h | 30.1 | 42.4 | 48.9 | 25.4 | 40.3 | 34.3 | 48.4 | 55.9 | 29.0 | 46.2 | 39.4 | 55.6 | 64.3 | 33.4 | 53.1 | 43.3 | 61.2 | 70.7 | 36.7 | 58.5 | 50.1 | 70.8 | 81.9 | 42.6 | 67.9 |
| RT-100U/SB in m3/h | 37.6 | 53.0 | 61.1 | 31.7 | 50.4 | 42.9 | 60.5 | 69.9 | 36.3 | 57.7 | 49.3 | 69.5 | 80.4 | 41.7 | 66.4 | 54.2 | 76.5 | 88.4 | 45.9 | 73.2 | 62.7 | 88.5 | 102.3 | 53.2 | 84.9 |
| RT-125U/SB in m3/h | 47.0 | 66.2 | 76.4 | 39.7 | 63.0 | 53.7 | 75.7 | 87.4 | 45.4 | 72.1 | 61.6 | 86.9 | 100.4 | 52.2 | 83.0 | 67.7 | 95.6 | 110.5 | 57.4 | 91.5 | 78.4 | 110.6 | 127.9 | 66.5 | 106.1 |
| RT-150U/SB in m3/h | 56.4 | 79.5 | 91.7 | 47.6 | 75.6 | 64.4 | 90.8 | 104.9 | 54.4 | 86.6 | 73.9 | 104.3 | 120.5 | 62.6 | 99.6 | 81.3 | 114.7 | 132.6 | 68.9 | 109.8 | 94.0 | 132.8 | 153.5 | 79.8 | 127.3 |
| RT-175U/SB in m3/h | 65.8 | 92.7 | 107.0 | 55.6 | 88.1 | 75.1 | 105.9 | 122.4 | 63.5 | 101.0 | 86.2 | 121.7 | 140.6 | 73.0 | 116.3 | 94.8 | 133.8 | 154.7 | 80.4 | 128.0 | 109.7 | 154.9 | 179.1 | 93.1 | 148.5 |
| RT-200U/SB in m3/h | 75.2 | 105.9 | 122.3 | 63.5 | 100.7 | 85.9 | 121.1 | 139.8 | 72.6 | 115.4 | 98.6 | 139.1 | 160.7 | 83.4 | 132.9 | 108.4 | 153.0 | 176.8 | 91.8 | 146.3 | 125.4 | 177.0 | 204.7 | 106.4 | 169.7 |
| RT-250U/SB in m3/h | 94.0 | 132.4 | 152.9 | 79.4 | 125.9 | 107.3 | 151.3 | 174.8 | 90.7 | 144.3 | 123.2 | 173.8 | 200.9 | 104.3 | 166.1 | 135.4 | 191.2 | 221.0 | 114.8 | 182.9 | 156.7 | 221.3 | 255.9 | 133.0 | 212.2 |
| RT-300U/SB in m3/h | 112.8 | 158.9 | 183.4 | 95.2 | 151.1 | 128.8 | 181.6 | 209.8 | 108.9 | 173.1 | 147.8 | 208.6 | 241.1 | 125.2 | 199.3 | 162.5 | 229.4 | 265.2 | 137.8 | 219.5 | 188.1 | 265.6 | 307.0 | 159.6 | 254.6 |
| RT-350U/SB in m3/h | 131.6 | 185.4 | 214.0 | 111.1 | 176.3 | 150.2 | 211.8 | 244.7 | 127.0 | 202.0 | 172.5 | 243.4 | 281.2 | 146.0 | 232.5 | 189.6 | 267.7 | 309.4 | 160.7 | 256.1 | 219.4 | 309.8 | 358.2 | 186.3 | 297.0 |
| RT-400U/SB in m3/h | 150.4 | 211.9 | 244.6 | 127.0 | 201.5 | 171.7 | 242.1 | 279.7 | 145.2 | 230.8 | 197.1 | 278.1 | 321.4 | 166.9 | 265.7 | 216.7 | 305.9 | 353.6 | 183.7 | 292.7 | 250.7 | 354.1 | 409.4 | 212.9 | 339.5 |
| RT-450U/SB in m3/h | 169.3 | 238.4 | 275.2 | 142.9 | 226.7 | 193.2 | 272.4 | 314.6 | 163.3 | 259.7 | 221.7 | 312.9 | 361.6 | 187.7 | 298.9 | 243.8 | 344.1 | 397.8 | 206.7 | 329.3 | 282.1 | 398.3 | 460.5 | 239.5 | 381.9 |
| RT-500U/SB in m3/h | 188.1 | 264.9 | 305.7 | 158.7 | 251.8 | 214.6 | 302.6 | 349.6 | 181.5 | 288.5 | 246.4 | 347.6 | 401.8 | 208.6 | 332.1 | 270.9 | 382.4 | 442.0 | 229.6 | 365.8 | 313.4 | 442.6 | 511.7 | 266.1 | 424.3 |

| Condition Reference # | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 |
|-----------------------------|------|------|------|------|------|------|------|------|------|------|------|------|-------|------|------|------|-------|-------|------|-------|------|-------|-------|------|-------|
| Wet Bulb °C | 10 | 10 | 10 | 10 | 10 | 13 | 13 | 13 | 13 | 13 | 16 | 16 | 16 | 16 | 16 | 18 | 18 | 18 | 18 | 18 | 21 | 21 | 21 | 21 | 21 |
| Range °C | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 |
| Approach °C | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 |
| Inlet Water Temperature °C | 20 | 22 | 23 | 22 | 25 | 23 | 25 | 26 | 25 | 28 | 26 | 28 | 29 | 28 | 31 | 28 | 30 | 31 | 30 | 33 | 31 | 33 | 34 | 33 | 36 |
| Outlet Water Temperature °C | 14 | 16 | 17 | 14 | 17 | 17 | 19 | 20 | 17 | 20 | 20 | 22 | 23 | 20 | 23 | 22 | 24 | 25 | 22 | 25 | 25 | 27 | 28 | 25 | 28 |
| RT-80U/SB in l/s | 8.4 | 11.8 | 13.6 | 7.1 | 11.2 | 9.5 | 13.5 | 15.5 | 8.1 | 12.8 | 11.0 | 15.5 | 17.9 | 9.3 | 14.8 | 12.0 | 17.0 | 19.6 | 10.2 | 16.3 | 13.9 | 19.7 | 22.7 | 11.8 | 18.9 |
| RT-100U/SB in l/s | 10.4 | 14.7 | 17.0 | 8.8 | 14.0 | 11.9 | 16.8 | 19.4 | 10.1 | 16.0 | 13.7 | 19.3 | 22.3 | 11.6 | 18.5 | 15.0 | 21.2 | 24.6 | 12.8 | 20.3 | 17.4 | 24.6 | 28.4 | 14.8 | 23.6 |
| RT-125U/SB in l/s | 13.1 | 18.4 | 21.2 | 11.0 | 17.5 | 14.9 | 21.0 | 24.3 | 12.6 | 20.0 | 17.1 | 24.1 | 27.9 | 14.5 | 23.1 | 18.8 | 26.6 | 30.7 | 15.9 | 25.4 | 21.8 | 30.7 | 35.5 | 18.5 | 29.5 |
| RT-150U/SB in l/s | 15.7 | 22.1 | 25.5 | 13.2 | 21.0 | 17.9 | 25.2 | 29.1 | 15.1 | 24.0 | 20.5 | 29.0 | 33.5 | 17.4 | 27.7 | 22.6 | 31.9 | 36.8 | 19.1 | 30.5 | 26.1 | 36.9 | 42.6 | 22.2 | 35.4 |
| RT-175U/SB in l/s | 18.3 | 25.8 | 29.7 | 15.4 | 24.5 | 20.9 | 29.4 | 34.0 | 17.6 | 28.1 | 24.0 | 33.8 | 39.1 | 20.3 | 32.3 | 26.3 | 37.2 | 43.0 | 22.3 | 35.6 | 30.5 | 43.0 | 49.7 | 25.9 | 41.3 |
| RT-200U/SB in l/s | 20.9 | 29.4 | 34.0 | 17.6 | 28.0 | 23.8 | 33.6 | 38.8 | 20.2 | 32.1 | 27.4 | 38.6 | 44.6 | 23.2 | 36.9 | 30.1 | 42.5 | 49.1 | 25.5 | 40.6 | 34.8 | 49.2 | 56.9 | 29.6 | 47.1 |
| RT-250U/SB in l/s | 26.1 | 36.8 | 42.5 | 22.0 | 35.0 | 29.8 | 42.0 | 48.6 | 25.2 | 40.1 | 34.2 | 48.3 | 55.8 | 29.0 | 46.1 | 37.6 | 53.1 | 61.4 | 31.9 | 50.8 | 43.5 | 61.5 | 71.1 | 37.0 | 58.9 |
| RT-300U/SB in l/s | 31.3 | 44.1 | 51.0 | 26.5 | 42.0 | 35.8 | 50.4 | 58.3 | 30.2 | 48.1 | 41.1 | 57.9 | 67.0 | 34.8 | 55.4 | 45.1 | 63.7 | 73.7 | 38.3 | 61.0 | 52.2 | 73.8 | 85.3 | 44.3 | 70.7 |
| RT-350U/SB in l/s | 36.6 | 51.5 | 59.4 | 30.9 | 49.0 | 41.7 | 58.8 | 68.0 | 35.3 | 56.1 | 47.9 | 67.6 | 78.1 | 40.6 | 64.6 | 52.7 | 74.4 | 85.9 | 44.6 | 71.1 | 60.9 | 86.1 | 99.5 | 51.7 | 82.5 |
| RT-400U/SB in l/s | 41.8 | 58.9 | 67.9 | 35.3 | 56.0 | 47.7 | 67.3 | 77.7 | 40.3 | 64.1 | 54.8 | 77.3 | 89.3 | 46.4 | 73.8 | 60.2 | 85.0 | 98.2 | 51.0 | 81.3 | 69.7 | 98.4 | 113.7 | 59.1 | 94.3 |
| RT-450U/SB in l/s | 47.0 | 66.2 | 76.4 | 39.7 | 63.0 | 53.7 | 75.7 | 87.4 | 45.4 | 72.1 | 61.6 | 86.9 | 100.4 | 52.2 | 83.0 | 67.7 | 95.6 | 110.5 | 57.4 | 91.5 | 78.4 | 110.6 | 127.9 | 66.5 | 106.1 |
| RT-500U/SB in l/s | 52.2 | 73.6 | 84.9 | 44.1 | 70.0 | 59.6 | 84.1 | 97.1 | 50.4 | 80.1 | 68.4 | 96.6 | 111.6 | 57.9 | 92.3 | 75.2 | 106.2 | 122.8 | 63.8 | 101.6 | 87.1 | 122.9 | 142.1 | 73.9 | 117.9 |

Ryoden RT-U, R1, 2016

| Condition Reference # | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Wet Bulb °C | 24 | 24 | 24 | 24 | 24 | 27 | 27 | 27 | 27 | 27 | 29 | 29 | 29 | 29 | 29 | 32.2 | 32.2 | 32.2 | 32.2 | 32.2 | 21 | 25.56 | 27 | 28 |
| Range °C | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 5 | 5.56 | 5 | 5 |
| Approach °C | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 6 | 3.89 | 5 | 4 |
| Inlet Water Temperature °C | 34 | 36 | 37 | 36 | 39 | 37 | 39 | 40 | 39 | 42 | 39 | 41 | 42 | 41 | 44 | 42.2 | 44.2 | 45.2 | 44.2 | 47.2 | 32 | 35.00 | 37 | 37 |
| Outlet Water Temperature °C | 28 | 30 | 31 | 28 | 31 | 31 | 33 | 34 | 31 | 34 | 33 | 35 | 36 | 33 | 36 | 36.2 | 38.2 | 39.2 | 36.2 | 39.2 | 27 | 29.44 | 32 | 32 |
| RT-80U/SB in m3/h | 58.3 | 82.3 | 95.2 | 49.5 | 79.1 | 67.9 | 96.0 | 111.0 | 57.9 | 92.4 | 75.4 | 106.5 | 123.2 | 64.3 | 102.7 | 89.4 | 126.3 | 146.1 | 76.4 | 122.0 | 80.2 | 64.5 | 91.8 | 80.0 |
| RT-100U/SB in m3/h | 72.8 | 102.9 | 119.0 | 61.9 | 98.8 | 84.9 | 120.0 | 138.7 | 72.3 | 115.5 | 94.3 | 133.1 | 154.0 | 80.4 | 128.3 | 111.8 | 157.8 | 182.6 | 95.4 | 152.5 | 100.3 | 80.6 | 114.8 | 100.0 |
| RT-125U/SB in m3/h | 91.0 | 128.6 | 148.7 | 77.4 | 123.5 | 106.2 | 149.9 | 173.4 | 90.4 | 144.3 | 117.8 | 166.4 | 192.5 | 100.5 | 160.4 | 139.7 | 197.3 | 228.2 | 119.3 | 190.6 | 125.4 | 100.7 | 143.5 | 125.0 |
| RT-150U/SB in m3/h | 109.2 | 154.3 | 178.4 | 92.9 | 148.2 | 127.4 | 179.9 | 208.1 | 108.5 | 173.2 | 141.4 | 199.7 | 231.0 | 120.6 | 192.5 | 167.6 | 236.7 | 273.9 | 143.2 | 228.7 | 150.4 | 120.9 | 172.2 | 150.0 |
| RT-175U/SB in m3/h | 127.4 | 180.0 | 208.2 | 108.4 | 172.9 | 148.6 | 209.9 | 242.8 | 126.6 | 202.1 | 165.0 | 233.0 | 269.5 | 140.6 | 224.6 | 195.6 | 276.2 | 319.5 | 167.0 | 266.8 | 175.5 | 141.0 | 200.9 | 175.0 |
| RT-200U/SB in m3/h | 145.6 | 205.7 | 237.9 | 123.8 | 197.6 | 169.9 | 239.9 | 277.5 | 144.6 | 230.9 | 188.5 | 266.3 | 308.0 | 160.7 | 256.7 | 223.5 | 315.7 | 365.2 | 190.9 | 304.9 | 200.6 | 161.1 | 229.6 | 200.0 |
| RT-250U/SB in m3/h | 182.1 | 257.1 | 297.4 | 154.8 | 247.0 | 212.3 | 299.9 | 346.9 | 180.8 | 288.7 | 235.7 | 332.9 | 385.0 | 200.9 | 320.8 | 279.4 | 394.6 | 456.5 | 238.6 | 381.1 | 250.7 | 201.4 | 287.0 | 250.0 |
| RT-300U/SB in m3/h | 218.5 | 308.6 | 356.9 | 185.8 | 296.5 | 254.8 | 359.9 | 416.2 | 217.0 | 346.4 | 282.8 | 399.4 | 462.1 | 241.1 | 385.0 | 335.3 | 473.5 | 547.8 | 286.3 | 457.4 | 300.9 | 241.7 | 344.4 | 300.0 |
| RT-350U/SB in m3/h | 254.9 | 360.0 | 416.3 | 216.7 | 345.9 | 297.2 | 419.8 | 485.6 | 253.1 | 404.1 | 329.9 | 466.0 | 539.1 | 281.3 | 449.2 | 391.1 | 552.4 | 639.1 | 334.0 | 533.6 | 351.0 | 282.0 | 401.8 | 350.0 |
| RT-400U/SB in m3/h | 291.3 | 411.4 | 475.8 | 247.7 | 395.3 | 339.7 | 479.8 | 555.0 | 289.3 | 461.9 | 377.1 | 532.6 | 616.1 | 321.5 | 513.3 | 447.0 | 631.3 | 730.4 | 381.8 | 609.8 | 401.1 | 322.3 | 459.2 | 400.0 |
| RT-450U/SB in m3/h | 327.7 | 462.9 | 535.3 | 278.6 | 444.7 | 382.2 | 539.8 | 624.4 | 325.4 | 519.6 | 424.2 | 599.2 | 693.1 | 361.7 | 577.5 | 502.9 | 710.2 | 821.7 | 429.5 | 686.1 | 451.3 | 362.6 | 516.6 | 450.0 |
| RT-500U/SB in m3/h | 364.1 | 514.3 | 594.8 | 309.6 | 494.1 | 424.6 | 599.8 | 693.7 | 361.6 | 577.3 | 471.4 | 665.7 | 770.1 | 401.8 | 641.7 | 558.8 | 789.2 | 913.0 | 477.2 | 762.3 | 501.4 | 402.9 | 574.1 | 500.0 |

| Condition Reference # | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 |
|-----------------------------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Wet Bulb °C | 24 | 24 | 24 | 24 | 24 | 27 | 27 | 27 | 27 | 27 | 29 | 29 | 29 | 29 | 29 | 32.2 | 32.2 | 32.2 | 32.2 | 32.2 | 21 | 25.56 | 27 | 28 |
| Range °C | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 6 | 6 | 6 | 8 | 8 | 5 | 5.56 | 5 | 5 |
| Approach °C | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 4 | 6 | 7 | 4 | 7 | 6 | 3.89 | 5 | 4 |
| Inlet Water Temperature °C | 34 | 36 | 37 | 36 | 39 | 37 | 39 | 40 | 39 | 42 | 39 | 41 | 42 | 41 | 44 | 42.2 | 44.2 | 45.2 | 44.2 | 47.2 | 32 | 35.00 | 37 | 37 |
| Outlet Water Temperature °C | 28 | 30 | 31 | 28 | 31 | 31 | 33 | 34 | 31 | 34 | 33 | 35 | 36 | 33 | 36 | 36.2 | 38.2 | 39.2 | 36.2 | 39.2 | 27 | 29.44 | 32 | 32 |
| RT-80U/SB in l/s | 16.2 | 22.9 | 26.4 | 13.8 | 22.0 | 18.9 | 26.7 | 30.8 | 16.1 | 25.7 | 20.9 | 29.6 | 34.2 | 17.9 | 28.5 | 24.8 | 35.1 | 40.6 | 21.2 | 33.9 | 22.3 | 17.9 | 25.5 | 22.2 |
| RT-100U/SB in l/s | 20.2 | 28.6 | 33.0 | 17.2 | 27.4 | 23.6 | 33.3 | 38.5 | 20.1 | 32.1 | 26.2 | 37.0 | 42.8 | 22.3 | 35.6 | 31.0 | 43.8 | 50.7 | 26.5 | 42.3 | 27.9 | 22.4 | 31.9 | 27.8 |
| RT-125U/SB in l/s | 25.3 | 35.7 | 41.3 | 21.5 | 34.3 | 29.5 | 41.7 | 48.2 | 25.1 | 40.1 | 32.7 | 46.2 | 53.5 | 27.9 | 44.6 | 38.8 | 54.8 | 63.4 | 33.1 | 52.9 | 34.8 | 28.0 | 39.9 | 34.7 |
| RT-150U/SB in l/s | 30.3 | 42.9 | 49.6 | 25.8 | 41.2 | 35.4 | 50.0 | 57.8 | 30.1 | 48.1 | 39.3 | 55.5 | 64.2 | 33.5 | 53.5 | 46.6 | 65.8 | 76.1 | 39.8 | 63.5 | 41.8 | 33.6 | 47.8 | 41.7 |
| RT-175U/SB in l/s | 35.4 | 50.0 | 57.8 | 30.1 | 48.0 | 41.3 | 58.3 | 67.4 | 35.2 | 56.1 | 45.8 | 64.7 | 74.9 | 39.1 | 62.4 | 54.3 | 76.7 | 88.8 | 46.4 | 74.1 | 48.8 | 39.2 | 55.8 | 48.6 |
| RT-200U/SB in l/s | 40.5 | 57.1 | 66.1 | 34.4 | 54.9 | 47.2 | 66.6 | 77.1 | 40.2 | 64.1 | 52.4 | 74.0 | 85.6 | 44.6 | 71.3 | 62.1 | 87.7 | 101.4 | 53.0 | 84.7 | 55.7 | 44.8 | 63.8 | 55.6 |
| RT-250U/SB in l/s | 50.6 | 71.4 | 82.6 | 43.0 | 68.6 | 59.0 | 83.3 | 96.4 | 50.2 | 80.2 | 65.5 | 92.5 | 107.0 | 55.8 | 89.1 | 77.6 | 109.6 | 126.8 | 66.3 | 105.9 | 69.6 | 56.0 | 79.7 | 69.4 |
| RT-300U/SB in l/s | 60.7 | 85.7 | 99.1 | 51.6 | 82.3 | 70.8 | 100.0 | 115.6 | 60.3 | 96.2 | 78.6 | 111.0 | 128.3 | 67.0 | 106.9 | 93.1 | 131.5 | 152.2 | 79.5 | 127.0 | 83.6 | 67.1 | 95.7 | 83.3 |
| RT-350U/SB in l/s | 70.8 | 100.0 | 115.7 | 60.2 | 96.1 | 82.6 | 116.6 | 134.9 | 70.3 | 112.3 | 91.7 | 129.4 | 149.7 | 78.1 | 124.8 | 108.7 | 153.4 | 177.5 | 92.8 | 148.2 | 97.5 | 78.3 | 111.6 | 97.2 |
| RT-400U/SB in l/s | 80.9 | 114.3 | 132.2 | 68.8 | 109.8 | 94.4 | 133.3 | 154.2 | 80.4 | 128.3 | 104.7 | 147.9 | 171.1 | 89.3 | 142.6 | 124.2 | 175.4 | 202.9 | 106.0 | 169.4 | 111.4 | 89.5 | 127.6 | 111.1 |
| RT-450U/SB in l/s | 91.0 | 128.6 | 148.7 | 77.4 | 123.5 | 106.2 | 149.9 | 173.4 | 90.4 | 144.3 | 117.8 | 166.4 | 192.5 | 100.5 | 160.4 | 139.7 | 197.3 | 228.2 | 119.3 | 190.6 | 125.4 | 100.7 | 143.5 | 125.0 |
| RT-500U/SB in l/s | 101.1 | 142.9 | 165.2 | 86.0 | 137.2 | 118.0 | 166.6 | 192.7 | 100.4 | 160.4 | 130.9 | 184.9 | 213.9 | 111.6 | 178.2 | 155.2 | 219.2 | 253.6 | 132.6 | 211.7 | 139.3 | 111.9 | 159.5 | 138.9 |