

**Elendoo ELN R0**

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
ELN-100TCU in m <sup>3</sup> /h	3.0	4.2	4.9	2.5	4.0	3.4	4.8	5.6	2.9	4.6	3.9	5.6	6.4	3.3	5.3	4.3	6.1	7.1	3.7	5.9	5.0	7.1	8.2	4.3	6.8
ELN-250TCU in m <sup>3</sup> /h	7.5	10.6	12.2	6.3	10.1	8.6	12.1	14.0	7.3	11.5	9.9	13.9	16.1	8.3	13.3	10.8	15.3	17.7	9.2	14.6	12.5	17.7	20.5	10.6	17.0
ELN-500TCU in m <sup>3</sup> /h	15.0	21.2	24.5	12.7	20.1	17.2	24.2	28.0	14.5	23.1	19.7	27.8	32.1	16.7	26.6	21.7	30.6	35.4	18.4	29.3	25.1	35.4	40.9	21.3	33.9
ELN-750TCU in m <sup>3</sup> /h	22.6	31.8	36.7	19.0	30.2	25.8	36.3	42.0	21.8	34.6	29.6	41.7	48.2	25.0	39.9	32.5	45.9	53.0	27.6	43.9	37.6	53.1	61.4	31.9	50.9
ELN-800TCU in m <sup>3</sup> /h	24.4	34.4	39.7	20.6	32.7	27.9	39.3	45.4	23.6	37.5	32.0	45.2	52.2	27.1	43.2	35.2	49.7	57.5	29.9	47.6	40.7	57.5	66.5	34.6	55.2
ELN-900TCU in m <sup>3</sup> /h	27.5	38.7	44.6	23.2	36.8	31.3	44.2	51.0	26.5	42.1	36.0	50.8	58.7	30.5	48.5	39.6	55.8	64.5	33.5	53.4	45.8	64.6	74.7	38.8	62.0
ELN-1000TCU in m <sup>3</sup> /h	30.5	42.9	49.5	25.7	40.8	34.8	49.0	56.6	29.4	46.7	39.9	56.3	65.1	33.8	53.8	43.9	61.9	71.6	37.2	59.3	50.8	71.7	82.9	43.1	68.7
ELN-1100TCU in m <sup>3</sup> /h	33.5	47.1	54.4	28.3	44.8	38.2	53.9	62.2	32.3	51.4	43.9	61.9	71.5	37.1	59.1	48.2	68.1	78.7	40.9	65.1	55.8	78.8	91.1	47.4	75.5
ELN-1250TCU in m <sup>3</sup> /h	38.0	53.5	61.8	32.1	50.9	43.4	61.1	70.6	36.7	58.3	49.8	70.2	81.2	42.1	67.1	54.7	77.2	89.3	46.4	73.9	63.3	89.4	103.4	53.7	85.7
ELN-1300TCU in m <sup>3</sup> /h	39.5	55.6	64.2	33.3	52.9	45.1	63.6	73.4	38.1	60.6	51.7	73.0	84.4	43.8	69.8	56.9	80.3	92.8	48.2	76.8	65.8	92.9	107.5	55.9	89.1
ELN-1500TCU in m <sup>3</sup> /h	45.5	64.1	74.0	38.4	60.9	51.9	73.2	84.6	43.9	69.8	59.6	84.1	97.2	50.5	80.4	65.6	92.5	107.0	55.6	88.5	75.9	107.1	123.8	64.4	102.7
ELN-1550TCU in m <sup>3</sup> /h	47.0	66.2	76.4	39.7	63.0	53.7	75.7	87.4	45.4	72.1	61.6	86.9	100.4	52.2	83.0	67.7	95.6	110.5	57.4	91.5	78.4	110.6	127.9	66.5	106.1
ELN-1750TCU in m <sup>3</sup> /h	53.0	74.7	86.2	44.8	71.0	60.5	85.3	98.6	51.2	81.4	69.5	98.0	113.3	58.8	93.7	76.4	107.8	124.6	64.8	103.2	88.4	124.8	144.3	75.0	119.7
ELN-1810TCU in m <sup>3</sup> /h	54.9	77.3	89.3	46.3	73.5	62.7	88.4	102.1	53.0	84.2	71.9	101.5	117.3	60.9	97.0	79.1	111.7	129.1	67.0	106.8	91.5	129.2	149.4	77.7	123.9
ELN-2000TCU in m <sup>3</sup> /h	60.6	85.3	98.4	51.1	81.1	69.1	97.5	112.6	58.4	92.9	79.3	111.9	129.4	67.2	107.0	87.2	123.1	142.3	73.9	117.8	100.9	142.5	164.8	85.7	136.6
ELN-2100TCU in m <sup>3</sup> /h	63.6	89.5	103.3	53.6	85.1	72.5	102.3	118.2	61.3	97.5	83.3	117.5	135.8	70.5	112.3	91.6	129.2	149.4	77.6	123.7	105.9	149.6	173.0	89.9	143.4
ELN-2500TCU in m <sup>3</sup> /h	76.0	107.0	123.5	64.1	101.7	86.7	122.3	141.2	73.3	116.6	99.5	140.4	162.3	84.3	134.2	109.4	154.5	178.6	92.8	147.8	126.6	178.8	206.7	107.5	171.4
ELN-2590TCU in m <sup>3</sup> /h	78.6	110.7	127.8	66.3	105.3	89.7	126.5	146.1	75.8	120.6	103.0	145.3	167.9	87.2	138.8	113.2	159.8	184.7	96.0	152.9	131.0	185.0	213.9	111.2	177.4
ELN-3000TCU in m <sup>3</sup> /h	91.0	128.2	148.0	76.8	121.9	103.9	146.5	169.2	87.8	139.6	119.2	168.3	194.5	101.0	160.8	131.1	185.1	213.9	111.1	177.1	151.7	214.2	247.7	128.8	205.4
ELN-3150TCU in m <sup>3</sup> /h	95.5	134.6	155.3	80.6	127.9	109.0	153.7	177.6	92.2	146.6	125.2	176.6	204.1	106.0	168.7	137.6	194.2	224.5	116.6	185.8	159.2	224.8	259.9	135.2	215.6

**Elendoo ELN R0**

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2		21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8		5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7		6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2		32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2		27	29.44	32	32
ELN-100TCU in m <sup>3</sup> /h	5.8	8.2	9.5	5.0	7.9	6.8	9.6	11.1	5.8	9.2	7.5	10.7	12.3	6.4	10.3	8.9	12.6	14.6	7.6	12.2		8.0	6.4	9.2	8
ELN-250TCU in m <sup>3</sup> /h	14.6	20.6	23.8	12.4	19.8	17.0	24.0	27.7	14.5	23.1	18.9	26.6	30.8	16.1	25.7	22.4	31.6	36.5	19.1	30.5		20.1	16.1	23.0	20
ELN-500TCU in m <sup>3</sup> /h	29.1	41.1	47.6	24.8	39.5	34.0	48.0	55.5	28.9	46.2	37.7	53.3	61.6	32.1	51.3	44.7	63.1	73.0	38.2	61.0		40.1	32.2	45.9	40
ELN-750TCU in m <sup>3</sup> /h	43.7	61.7	71.4	37.2	59.3	51.0	72.0	83.2	43.4	69.3	56.6	79.9	92.4	48.2	77.0	67.1	94.7	109.6	57.3	91.5		60.2	48.3	68.9	60
ELN-800TCU in m <sup>3</sup> /h	47.3	66.9	77.3	40.2	64.2	55.2	78.0	90.2	47.0	75.1	61.3	86.5	100.1	52.2	83.4	72.6	102.6	118.7	62.0	99.1		65.2	52.4	74.6	65
ELN-900TCU in m <sup>3</sup> /h	53.2	75.1	86.8	45.2	72.1	62.0	87.6	101.3	52.8	84.3	68.8	97.2	112.4	58.7	93.7	81.6	115.2	133.3	69.7	111.3		73.2	58.8	83.8	73
ELN-1000TCU in m <sup>3</sup> /h	59.0	83.3	96.4	50.2	80.0	68.8	97.2	112.4	58.6	93.5	76.4	107.8	124.8	65.1	104.0	90.5	127.8	147.9	77.3	123.5		81.2	65.3	93.0	81
ELN-1100TCU in m <sup>3</sup> /h	64.8	91.5	105.9	55.1	87.9	75.6	106.8	123.5	64.4	102.8	83.9	118.5	137.1	71.5	114.2	99.5	140.5	162.5	84.9	135.7		89.3	71.7	102.2	89
ELN-1250TCU in m <sup>3</sup> /h	73.6	103.9	120.1	62.5	99.8	85.8	121.2	140.1	73.0	116.6	95.2	134.5	155.6	81.2	129.6	112.9	159.4	184.4	96.4	154.0		101.3	81.4	116.0	101
ELN-1300TCU in m <sup>3</sup> /h	76.5	108.0	124.9	65.0	103.8	89.2	126.0	145.7	75.9	121.2	99.0	139.8	161.7	84.4	134.8	117.3	165.7	191.7	100.2	160.1		105.3	84.6	120.6	105
ELN-1500TCU in m <sup>3</sup> /h	88.1	124.5	143.9	74.9	119.6	102.8	145.1	167.9	87.5	139.7	114.1	161.1	186.4	97.2	155.3	135.2	191.0	220.9	115.5	184.5		121.3	97.5	138.9	121
ELN-1550TCU in m <sup>3</sup> /h	91.0	128.6	148.7	77.4	123.5	106.2	149.9	173.4	90.4	144.3	117.8	166.4	192.5	100.5	160.4	139.7	197.3	228.2	119.3	190.6		125.4	100.7	143.5	125
ELN-1750TCU in m <sup>3</sup> /h	102.7	145.0	167.7	87.3	139.3	119.7	169.1	195.6	102.0	162.8	132.9	187.7	217.2	113.3	181.0	157.6	222.5	257.5	134.6	215.0		141.4	113.6	161.9	141
ELN-1810TCU in m <sup>3</sup> /h	106.3	150.2	173.7	90.4	144.3	124.0	175.1	202.6	105.6	168.6	137.6	194.4	224.9	117.3	187.4	163.2	230.4	266.6	139.3	222.6		146.4	117.6	167.6	146
ELN-2000TCU in m <sup>3</sup> /h	117.2	165.6	191.5	99.7	159.1	136.7	193.1	223.4	116.4	185.9	151.8	214.4	248.0	129.4	206.6	179.9	254.1	294.0	153.7	245.5		161.5	129.7	184.8	161
ELN-2100TCU in m <sup>3</sup> /h	123.1	173.8	201.0	104.6	167.0	143.5	202.7	234.5	122.2	195.1	159.3	225.0	260.3	135.8	216.9	188.9	266.7	308.6	161.3	257.7		169.5	136.2	194.0	169
ELN-2500TCU in m <sup>3</sup> /h	147.1	207.8	240.3	125.1	199.6	171.5	242.3	280.3	146.1	233.2	190.4	269.0	311.1	162.3	259.2	225.7	318.8	368.8	192.8	308.0		202.6	162.8	231.9	202
ELN-2590TCU in m <sup>3</sup> /h	152.2	215.0	248.6	129.4	206.5	177.5	250.7	290.0	151.1	241.3	197.0	278.3	321.9	168.0	268.2	233.6	329.9	381.6	199.5	318.6		209.6	168.4	240.0	209
ELN-3000TCU in m <sup>3</sup> /h	176.2	248.9	287.9	149.8	239.1	205.5	290.3	335.8	175.0	279.4	228.1	322.2	372.7	194.5	310.6	270.5	381.9	441.9	231.0	368.9		242.7	195.0	277.8	242
ELN-3150TCU in m <sup>3</sup> /h	185.0	261.3	302.1	157.3	251.0	215.7	304.7	352.4	183.7	293.3	239.4	338.2	391.2	204.1	326.0	283.9	400.9	463.8	242.4	387.2		254.7	204.7	291.6	254