

**Guangdong Feiyang LK Series R0**

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
LK-1800-4 in m3/h	37.6	53.0	61.1	31.7	50.4	42.9	60.5	69.9	36.3	57.7	49.3	69.5	80.4	41.7	66.4	54.2	76.5	88.4	45.9	73.2	62.7	88.5	102.3	53.2	84.9
LK-2100-5.5 in m3/h	56.4	79.5	91.7	47.6	75.6	64.4	90.8	104.9	54.4	86.6	73.9	104.3	120.5	62.6	99.6	81.3	114.7	132.6	68.9	109.8	94.0	132.8	153.5	79.8	127.3
LK-2400-5.5 in m3/h	75.2	105.9	122.3	63.5	100.7	85.9	121.1	139.8	72.6	115.4	98.6	139.1	160.7	83.4	132.9	108.4	153.0	176.8	91.8	146.3	125.4	177.0	204.7	106.4	169.7
LK-2600-7.5 in m3/h	94.0	132.4	152.9	79.4	125.9	107.3	151.3	174.8	90.7	144.3	123.2	173.8	200.9	104.3	166.1	135.4	191.2	221.0	114.8	182.9	156.7	221.3	255.9	133.0	212.2

**Guangdong Feiyang LK Series R0**

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
LK-1800-4 in m3/h	72.8	102.9	119.0	61.9	98.8	84.9	120.0	138.7	72.3	115.5	94.3	133.1	154.0	80.4	128.3	111.8	157.8	182.6	95.4	152.5	100.3	80.6	114.8	100
LK-2100-5.5 in m3/h	109.2	154.3	178.4	92.9	148.2	127.4	179.9	208.1	108.5	173.2	141.4	199.7	231.0	120.6	192.5	167.6	236.7	273.9	143.2	228.7	150.4	120.9	172.2	150
LK-2400-5.5 in m3/h	145.6	205.7	237.9	123.8	197.6	169.9	239.9	277.5	144.6	230.9	188.5	266.3	308.0	160.7	256.7	223.5	315.7	365.2	190.9	304.9	200.6	161.1	229.6	200
LK-2600-7.5 in m3/h	182.1	257.1	297.4	154.8	247.0	212.3	299.9	346.9	180.8	288.7	235.7	332.9	385.0	200.9	320.8	279.4	394.6	456.5	238.6	381.1	250.7	201.4	287.0	250