

i-Tower REH R0 2016

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
REH1015Z2 in m3/h	8.5	12.0	13.9	7.2	11.4	9.7	13.7	15.9	8.2	13.1	11.2	15.8	18.2	9.5	15.1	12.3	17.4	20.1	10.4	16.6	14.2	20.1	23.2	12.1	19.3
REH1019Z2 in m3/h	10.2	14.4	16.7	8.6	13.7	11.7	16.5	19.0	9.9	15.7	13.4	18.9	21.9	11.4	18.1	14.8	20.8	24.1	12.5	19.9	17.1	24.1	27.9	14.5	23.1
REH1119Z2 in m3/h	12.0	16.8	19.4	10.1	16.0	13.6	19.2	22.2	11.5	18.3	15.7	22.1	25.5	13.3	21.1	17.2	24.3	28.1	14.6	23.3	19.9	28.1	32.5	16.9	27.0
REH1023Z3 in m3/h	13.7	19.2	22.2	11.5	18.3	15.6	22.0	25.4	13.2	21.0	17.9	25.3	29.2	15.2	24.1	19.7	27.8	32.1	16.7	26.6	22.8	32.2	37.2	19.3	30.8
REH1123Z3 in m3/h	17.1	24.1	27.8	14.4	22.9	19.5	27.5	31.7	16.5	26.2	22.4	31.6	36.5	18.9	30.2	24.6	34.7	40.1	20.9	33.2	28.5	40.2	46.5	24.2	38.5
REH1223Y3 in m3/h	22.2	31.3	36.1	18.7	29.7	25.3	35.7	41.3	21.4	34.1	29.1	41.0	47.4	24.6	39.2	32.0	45.1	52.2	27.1	43.2	37.0	52.2	60.4	31.4	50.1
REH1032Y4 in m3/h	27.3	38.5	44.4	23.1	36.6	31.2	44.0	50.8	26.4	41.9	35.8	50.5	58.4	30.3	48.3	39.4	55.6	64.2	33.4	53.2	45.5	64.3	74.3	38.7	61.7
REH1132Y4 in m3/h	30.7	43.3	50.0	25.9	41.2	35.1	49.5	57.1	29.7	47.2	40.3	56.8	65.7	34.1	54.3	44.3	62.5	72.2	37.5	59.8	51.2	72.3	83.6	43.5	69.4
REH1232Y4 in m3/h	34.2	48.1	55.5	28.8	45.7	39.0	55.0	63.5	33.0	52.4	44.7	63.1	73.0	37.9	60.3	49.2	69.4	80.3	41.7	66.4	56.9	80.4	92.9	48.3	77.1
REH1332Y4 in m3/h	37.6	52.9	61.1	31.7	50.3	42.9	60.5	69.8	36.3	57.6	49.2	69.5	80.3	41.7	66.4	54.1	76.4	88.3	45.9	73.1	62.6	88.4	102.2	53.2	84.8
REH1037Y4 in m3/h	42.7	60.1	69.4	36.0	57.2	48.7	68.7	79.4	41.2	65.5	55.9	78.9	91.2	47.4	75.4	61.5	86.8	100.3	52.1	83.1	71.2	100.5	116.2	60.4	96.3
REH1044X4 in m3/h	51.2	72.2	83.3	43.2	68.6	58.5	82.4	95.2	49.4	78.6	67.1	94.7	109.5	56.8	90.5	73.8	104.2	120.4	62.6	99.7	85.4	120.6	139.4	72.5	115.6
REH1144X4 in m3/h	59.8	84.2	97.2	50.4	80.0	68.2	96.2	111.1	57.7	91.7	78.3	110.5	127.7	66.3	105.6	86.1	121.5	140.5	73.0	116.3	99.6	140.7	162.6	84.6	134.9
REH1048W4 in m3/h	68.3	96.2	111.1	57.7	91.5	78.0	109.9	127.0	65.9	104.8	89.5	126.3	145.9	75.8	120.6	98.4	138.9	160.5	83.4	132.9	113.9	160.8	185.9	96.6	154.1
REH1148W4 in m3/h	76.8	108.2	124.9	64.9	102.9	87.7	123.7	142.9	74.2	117.9	100.7	142.1	164.2	85.2	135.7	110.7	156.3	180.6	93.8	149.5	128.1	180.9	209.1	108.7	173.4
REH1054W4 in m3/h	85.4	120.3	138.8	72.1	114.3	97.5	137.4	158.7	82.4	131.0	111.9	157.8	182.4	94.7	150.8	123.0	173.6	200.7	104.3	166.1	142.3	201.0	232.3	120.8	192.7
REH1154W4 in m3/h	93.9	132.3	152.7	79.3	125.8	107.2	151.2	174.6	90.6	144.1	123.1	173.6	200.7	104.2	165.9	135.3	191.0	220.7	114.7	182.7	156.5	221.1	255.6	132.9	211.9
REH1254W4 in m3/h	102.5	144.3	166.6	86.5	137.2	116.9	164.9	190.5	98.9	157.2	134.2	189.4	218.9	113.7	181.0	147.6	208.3	240.8	125.1	199.3	170.8	241.2	278.8	145.0	231.2

i-Tower REH R0 2016

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
REH1015Z2 in m3/h	16.5	23.4	27.0	14.1	22.4	19.3	27.2	31.5	16.4	26.2	21.4	30.2	35.0	18.2	29.1	25.4	35.8	41.5	21.7	34.6	22.8	18.3	26.1	23
REH1019Z2 in m3/h	19.8	28.0	32.4	16.9	26.9	23.1	32.7	37.8	19.7	31.5	25.7	36.3	42.0	21.9	35.0	30.4	43.0	49.7	26.0	41.5	27.3	22.0	31.3	27
REH1119Z2 in m3/h	23.1	32.7	37.8	19.7	31.4	27.0	38.1	44.1	23.0	36.7	30.0	42.3	49.0	25.5	40.8	35.5	50.2	58.0	30.3	48.5	31.9	25.6	36.5	32
REH1023Z3 in m3/h	26.5	37.4	43.2	22.5	35.9	30.8	43.6	50.4	26.3	41.9	34.2	48.4	55.9	29.2	46.6	40.6	57.3	66.3	34.7	55.4	36.4	29.3	41.7	36
REH1123Z3 in m3/h	33.1	46.7	54.0	28.1	44.9	38.6	54.5	63.0	32.8	52.4	42.8	60.5	69.9	36.5	58.3	50.7	71.7	82.9	43.3	69.2	45.5	36.6	52.1	45
REH1223Y3 in m3/h	43.0	60.7	70.2	36.5	58.3	50.1	70.8	81.9	42.7	68.2	55.6	78.6	90.9	47.4	75.8	66.0	93.2	107.8	56.3	90.0	59.2	47.6	67.8	59
REH1032Y4 in m3/h	52.9	74.7	86.4	45.0	71.8	61.7	87.1	100.8	52.5	83.9	68.5	96.7	111.9	58.4	93.2	81.2	114.7	132.7	69.3	110.8	72.9	58.5	83.4	73
REH1132Y4 in m3/h	59.5	84.1	97.2	50.6	80.8	69.4	98.0	113.4	59.1	94.4	77.0	108.8	125.9	65.7	104.9	91.3	129.0	149.2	78.0	124.6	82.0	65.9	93.8	82
REH1232Y4 in m3/h	66.1	93.4	108.0	56.2	89.7	77.1	108.9	126.0	65.7	104.9	85.6	120.9	139.9	73.0	116.5	101.5	143.3	165.8	86.7	138.4	91.1	73.2	104.3	91
REH1332Y4 in m3/h	72.7	102.7	118.8	61.8	98.7	84.8	119.8	138.6	72.2	115.3	94.2	133.0	153.9	80.3	128.2	111.6	157.7	182.4	95.3	152.3	100.2	80.5	114.7	100
REH1037Y4 in m3/h	82.7	116.8	135.0	70.3	112.2	96.4	136.2	157.5	82.1	131.1	107.0	151.1	174.8	91.2	145.7	126.9	179.2	207.3	108.3	173.1	113.8	91.5	130.3	114
REH1044X4 in m3/h	99.2	140.1	162.0	84.3	134.6	115.7	163.4	189.0	98.5	157.3	128.4	181.4	209.8	109.5	174.8	152.2	215.0	248.7	130.0	207.7	136.6	109.8	156.4	136
REH1144X4 in m3/h	115.7	163.5	189.0	98.4	157.0	135.0	190.6	220.5	114.9	183.5	149.8	211.6	244.8	127.7	203.9	177.6	250.8	290.2	151.7	242.3	159.4	128.0	182.5	159
REH1048W4 in m3/h	132.3	186.8	216.0	112.5	179.5	154.2	217.9	252.0	131.3	209.7	171.2	241.8	279.7	146.0	233.1	203.0	286.7	331.6	173.3	276.9	182.1	146.3	208.5	182
REH1148W4 in m3/h	148.8	210.2	243.1	126.5	201.9	173.5	245.1	283.5	147.8	235.9	192.6	272.0	314.7	164.2	262.2	228.3	322.5	373.1	195.0	311.5	204.9	164.6	234.6	204
REH1054W4 in m3/h	165.3	233.5	270.1	140.6	224.3	192.8	272.3	315.0	164.2	262.1	214.0	302.3	349.7	182.5	291.4	253.7	358.3	414.5	216.7	346.1	227.7	182.9	260.6	227
REH1154W4 in m3/h	181.9	256.9	297.1	154.6	246.8	212.1	299.6	346.5	180.6	288.3	235.4	332.5	384.6	200.7	320.5	279.1	394.1	456.0	238.3	380.7	250.4	201.2	286.7	250
REH1254W4 in m3/h	198.4	280.2	324.1	168.7	269.2	231.4	326.8	378.0	197.0	314.6	256.8	362.7	419.6	218.9	349.6	304.5	430.0	497.4	260.0	415.3	273.2	219.5	312.8	272