

OTT Co., Ltd. OTTC-L

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36	
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28	
<b>RATING FACTOR</b>	<b>0.3276</b>	<b>0.4614</b>	<b>0.5326</b>	<b>0.2765</b>	<b>0.4387</b>	<b>0.3739</b>	<b>0.5272</b>	<b>0.609</b>	<b>0.3161</b>	<b>0.5026</b>	<b>0.4292</b>	<b>0.6056</b>	<b>0.6999</b>	<b>0.3634</b>	<b>0.5786</b>	<b>0.4719</b>	<b>0.6661</b>	<b>0.7699</b>	<b>0.4</b>	<b>0.6373</b>	<b>0.546</b>	<b>0.771</b>	<b>0.8914</b>	<b>0.4635</b>	<b>0.7392</b>	
OTTC-125L	8.9	12.5	14.4	7.5	11.9	10.1	14.3	16.5	8.6	13.6	11.6	16.4	19.0	9.8	15.7	12.8	18.0	20.9	10.8	17.3	14.8	20.9	24.1	12.6	20.0	
OTTC-150L	10.6	15.0	17.3	9.0	14.3	12.2	17.1	19.8	10.3	16.3	13.9	19.7	22.7	11.8	18.8	15.3	21.6	25.0	13.0	20.7	17.7	25.1	29.0	15.1	24.0	
OTTC-175L	12.4	17.5	20.2	10.5	16.6	14.2	20.0	23.1	12.0	19.1	16.3	23.0	26.5	13.8	21.9	17.9	25.3	29.2	15.2	24.2	20.7	29.2	33.8	17.6	28.0	
OTTC-200L	14.2	20.0	23.1	12.0	19.0	16.2	22.8	26.4	13.7	21.8	18.6	26.2	30.3	15.7	25.1	20.4	28.9	33.4	17.3	27.6	23.7	33.4	38.6	20.1	32.0	
OTTC-225L	16.0	22.5	26.0	13.5	21.4	18.2	25.7	29.7	15.4	24.5	20.9	29.5	34.1	17.7	28.2	23.0	32.5	37.5	19.5	31.1	26.6	37.6	43.5	22.6	36.0	
OTTC-250L	17.7	25.0	28.8	15.0	23.8	20.3	28.6	33.0	17.1	27.2	23.2	32.8	37.9	19.7	31.3	25.6	36.1	41.7	21.7	34.5	29.6	41.8	48.3	25.1	40.0	
OTTC-275L	19.5	27.5	31.7	16.5	26.1	22.3	31.4	36.3	18.8	29.9	25.6	36.1	41.7	21.7	34.5	28.1	39.7	45.9	23.8	38.0	32.5	45.9	53.1	27.6	44.0	
OTTC-300L	21.3	30.0	34.6	18.0	28.5	24.3	34.3	39.6	20.5	32.7	27.9	39.4	45.5	23.6	37.6	30.7	43.3	50.0	26.0	41.4	35.5	50.1	57.9	30.1	48.0	
OTTC-330L	24.8	35.0	40.4	21.0	33.3	28.4	40.0	46.2	24.0	38.1	32.5	45.9	53.1	27.6	43.9	35.8	50.5	58.4	30.3	48.3	41.4	58.5	67.6	35.1	56.1	
OTTC-350L	24.8	35.0	40.4	21.0	33.3	28.4	40.0	46.2	24.0	38.1	32.5	45.9	53.1	27.6	43.9	35.8	50.5	58.4	30.3	48.3	41.4	58.5	67.6	35.1	56.1	
OTTC-400L	28.4	40.0	46.2	24.0	38.0	32.4	45.7	52.8	27.4	43.6	37.2	52.5	60.7	31.5	50.1	40.9	57.7	66.7	34.7	55.2	47.3	66.8	77.3	40.2	64.1	
OTTC-450L	31.9	45.0	51.9	27.0	42.8	36.5	51.4	59.4	30.8	49.0	41.8	59.0	68.2	35.4	56.4	46.0	64.9	75.1	39.0	62.1	53.2	75.2	86.9	45.2	72.1	
OTTC-500L	35.5	50.0	57.7	30.0	47.5	40.5	57.1	66.0	34.2	54.4	46.5	65.6	75.8	39.4	62.7	51.1	72.2	83.4	43.3	69.0	59.2	83.5	96.6	50.2	80.1	
OTTC-550L	39.0	55.0	63.5	32.9	52.3	44.6	62.8	72.6	37.7	59.9	51.1	72.2	83.4	43.3	68.9	56.2	79.4	91.7	47.7	75.9	65.1	91.9	106.2	55.2	88.1	
OTTC-600L	42.6	60.0	69.2	35.9	57.0	48.6	68.5	79.2	41.1	65.3	55.8	78.7	91.0	47.2	75.2	61.3	86.6	100.1	52.0	82.8	71.0	100.2	115.9	60.3	96.1	
OTTC-700L	49.7	70.0	80.8	41.9	66.5	56.7	80.0	92.4	47.9	76.2	65.1	91.8	106.2	55.1	87.8	71.6	101.0	116.8	60.7	96.7	82.8	116.9	135.2	70.3	112.1	
OTTC-800L	56.8	80.0	92.3	47.9	76.0	64.8	91.4	105.6	54.8	87.1	74.4	105.0	121.3	63.0	100.3	81.8	115.5	133.4	69.3	110.5	94.6	133.6	154.5	80.3	128.1	
OTTC-900L	63.9	90.0	103.9	53.9	85.5	72.9	102.8	118.8	61.6	98.0	83.7	118.1	136.5	70.9	112.8	92.0	129.9	150.1	78.0	124.3	106.5	150.3	173.8	90.4	144.1	
OTTC-1000L	71.0	100.0	115.4	59.9	95.1	81.0	114.2	132.0	68.5	108.9	93.0	131.2	151.6	78.7	125.4	102.2	144.3	166.8	86.7	138.1	118.3	167.1	193.1	100.4	160.2	
OTTC-1100L	78.1	110.0	126.9	65.9	104.6	89.1	125.6	145.1	75.3	119.8	102.3	144.3	166.8	86.6	137.9	112.5	158.8	183.5	95.3	151.9	130.1	183.8	212.5	110.5	176.2	
OTTC-1200L	85.2	120.0	138.5	71.9	114.1	97.2	137.1	158.3	82.2	130.7	111.6	157.5	182.0	94.5	150.4	122.7	173.2	200.2	104.0	165.7	142.0	200.5	231.8	120.5	192.2	
OTTC-1300L	92.3	130.0	150.0	77.9	123.6	105.3	148.5	171.5	89.0	141.6	120.9	170.6	197.1	102.4	163.0	132.9	187.6	216.9	112.7	179.5	153.8	217.2	251.1	130.6	208.2	
OTTC-1400L	99.4	140.0	161.6	83.9	133.1	113.4	159.9	184.7	95.9	152.5	130.2	183.7	212.3	110.2	175.5	143.1	202.1	233.5	121.3	193.3	165.6	233.9	270.4	140.6	224.2	
OTTC-1500L	106.5	150.0	173.1	89.9	142.6	121.5	171.3	197.9	102.7	163.3	139.5	196.8	227.5	118.1	188.0	153.4	216.5	250.2	130.0	207.1	177.5	250.6	289.7	150.6	240.2	
OTTC-1650L	117.1	165.0	190.4	98.8	156.8	133.7	188.5	217.7	113.0	179.7	153.4	216.5	250.2	129.9	206.8	168.7	238.1	275.2	143.0	227.8	195.2	275.6	318.7	165.7	264.3	
OTTC-1600L	113.6	160.0	184.6	95.9	152.1	129.6	182.8	211.1	109.6	174.2	148.8	209.9	242.6	126.0	200.6	163.6	230.9	266.9	138.7	220.9	189.3	267.3	309.0	160.7	256.3	
OTTC-1750L	124.2	174.9	201.9	104.8	166.3	141.8	199.9	230.9	119.9	190.6	162.7	229.6	265.4	137.8	219.4	178.9	252.6	291.9	151.7	241.6	207.0	292.3	338.0	175.7	280.3	

OTT Co., Ltd. OTTC-L

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32	32	32	32	32	32	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	8	8	8	5	5.56	5	5	
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4	
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.0	44.0	45.0	44.0	47.0	32	35.00	37	37	
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.0	38.0	39.0	36.0	39.0	27	29.44	32	32	
<b>RATING FACTOR</b>	<b>0.6343</b>	<b>0.8959</b>	<b>1.0361</b>	<b>0.5393</b>	<b>0.8607</b>	<b>0.7397</b>	<b>1.0448</b>	<b>1.2085</b>	<b>0.6299</b>	<b>1.0057</b>	<b>0.8211</b>	<b>1.1597</b>	<b>1.3415</b>	<b>0.7</b>	<b>1.1178</b>	<b>0.963</b>	<b>1.36</b>	<b>1.5734</b>	<b>0.8223</b>	<b>1.3135</b>	<b>0.8735</b>	<b>0.7018</b>	<b>1</b>	<b>0.871</b>	
OTTC-125L	17.2	24.3	28.1	14.6	23.3	20.0	28.3	32.7	17.1	27.2	22.2	31.4	36.3	19.0	30.3	26.1	36.8	42.6	22.3	35.6	23.7	19.0	27.1	23.6	
OTTC-150L	20.6	29.1	33.7	17.5	28.0	24.0	34.0	39.3	20.5	32.7	26.7	37.7	43.6	22.8	36.3	31.3	44.2	51.1	26.7	42.7	28.4	22.8	32.5	28.3	
OTTC-175L	24.1	34.0	39.3	20.4	32.6	28.0	39.6	45.8	23.9	38.1	31.1	44.0	50.9	26.5	42.4	36.5	51.6	59.7	31.2	49.8	33.1	26.6	37.9	33.0	
OTTC-200L	27.5	38.8	44.9	23.4	37.3	32.1	45.3	52.4	27.3	43.6	35.6	50.3	58.1	30.3	48.4	41.7	58.9	68.2	35.6	56.9	37.9	30.4	43.3	37.7	
OTTC-225L	30.9	43.7	50.5	26.3	42.0	36.1	50.9	58.9	30.7	49.0	40.0	56.5	65.4	34.1	54.5	46.9	66.3	76.7	40.1	64.0	42.6	34.2	48.8	42.5	
OTTC-250L	34.4	48.5	56.1	29.2	46.6	40.1	56.6	65.5	34.1	54.5	44.5	62.8	72.7	37.9	60.5	52.2	73.7	85.2	44.5	71.1	47.3	38.0	54.2	47.2	
OTTC-275L	37.8	53.4	61.7	32.1	51.3	44.1	62.3	72.0	37.5	59.9	48.9	69.1	79.9	41.7	66.6	57.4	81.0	93.7	49.0	78.3	52.0	41.8	59.6	51.9	
OTTC-300L	41.2	58.2	67.3	35.1	55.9	48.1	67.9	78.6	40.9	65.4	53.4	75.4	87.2	45.5	72.7	62.6	88.4	102.3	53.4	85.4	56.8	45.6	65.0	56.6	
OTTC-330L	44.1	62.9	72.6	37.9	59.7	50.9	71.7	83.4	43.7	69.3	57.3	80.3	94.1	48.8	78.6	66.6	95.4	111.3	57.3	91.3	60.6	49.6	70.0	62.1	
OTTC-350L	48.1	67.9	78.6	40.9	65.3	56.1	79.2	91.6	47.8	76.3	62.3	87.9	101.7	53.1	84.8	73.0	103.1	119.3	62.4	99.6	66.2	53.2	75.8	66.1	
OTTC-400L	55.0	77.6	89.8	46.7	74.6	64.1	90.5	104.7	54.6	87.2	71.2	100.5	116.3	60.7	96.9	83.5	117.9	136.4	71.3	113.8	75.7	60.8	86.7	75.5	
OTTC-450L	61.8	87.4	101.0	52.6	83.9	72.1	101.9	117.8	61.4	98.1	80.1	113.1	130.8	68.3	109.0	93.9	132.6	153.4	80.2	128.1	85.2	68.4	97.5	84.9	
OTTC-500L	68.7	97.1	112.2	58.4	93.2	80.1	113.2	130.9	68.2	109.0	89.0	125.6	145.3	75.8	121.1	104.3	147.3	170.5	89.1	142.3	94.6	76.0	108.3	94.4	
OTTC-550L	75.6	106.8	123.5	64.3	102.6	88.1	124.5	144.0	75.1	119.8	97.8	138.2	159.9	83.4	133.2	114.8	162.1	187.5	98.0	156.5	104.1	83.6	119.2	103.8	
OTTC-600L	82.5	116.5	134.7	70.1	111.9	96.2	135.8	157.1	81.9	130.7	106.7	150.8	174.4	91.0	145.3	125.2	176.8	204.5	106.9	170.8	113.6	91.2	130.0	113.2	
OTTC-700L	96.2	135.9	157.1	81.8	130.5	112.2	158.5	183.3	95.5	152.5	124.5	175.9	203.5	106.2	169.5	146.1	206.3	238.6	124.7	199.2	132.5	106.4	151.7	132.1	
OTTC-800L	109.9	155.3	179.6	93.5	149.2	128.2	181.1	209.5	109.2	174.3	142.3	201.0	232.5	121.3	193.8	166.9	235.7	272.7	142.5	227.7	151.4	121.6	173.3	151.0	
OTTC-900L	123.7	174.7	202.0	105.2	167.8	144.2	203.7	235.7	122.8	196.1	160.1	226.1	261.6	136.5	218.0	187.8	265.2	306.8	160.3	256.1	170.3	136.9	195.0	169.8	
OTTC-1000L	137.4	194.1	224.5	116.8	186.5	160.3	226.4	261.8	136.5	217.9	177.9	251.3	290.7	151.7	242.2	208.7	294.7	340.9	178.2	284.6	189.3	152.1	216.7	188.7	
OTTC-1100L	151.2	213.5	246.9	128.5	205.1	176.3	249.0	288.0	150.1	239.7	195.7	276.4	319.7	166.8	266.4	229.5	324.1	375.0	196.0	313.1	208.2	167.3	238.3	207.6	
OTTC-1200L	164.9	232.9	269.4	140.2	223.8	192.3	271.6	314.2	163.8	261.5	213.5	301.5	348.8	182.0	290.6	250.4	353.6	409.1	213.8	341.5	227.1	182.5	260.0	226.5	
OTTC-1300L	178.7	252.3	291.8	151.9	242.4	208.3	294.3	340.4	177.4	283.3	231.3	326.6	377.9	197.2	314.8	271.2	383.1	443.2	231.6	370.0	246.0	197.7	281.7	245.3	
OTTC-1400L	192.4	271.8	314.3	163.6	261.1	224.4	316.9	366.6	191.1	305.1	249.1	351.8	406.9	212.3	339.1	292.1	412.5	477.3	249.4	398.4	265.0	212.9	303.3	264.2	
OTTC-1500L	206.1	291.2	336.7	175.3	279.7	240.4	339.6	392.8	204.7	326.9	266.9	376.9	436.0	227.5	363.3	313.0	442.0	511.4	267.2	426.9	283.9	228.1	325.0	283.1	
OTTC-1650L	226.8	320.3	370.4	192.8	307.7	264.4	373.5	432.0	225.2	359.5	293.5	414.6	479.6	250.3	399.6	344.3	486.2	562.5	294.0	469.6	312.3	250.9	357.5	311.4	
OTTC-1600L	219.9	310.6	359.2	187.0	298.4	256.4	362.2	418.9	218.4	348.6	284.6	402.0	465.1	242.7	387.5	333.8	471.5	545.4	285.1	455.3	302.8	243.3	346.7	301.9	
OTTC-1750L	240.5	339.7	392.9	204.5	326.3	280.5	396.2	458.2	238.8	381.3	311.3	439.7	508.7	265.4	423.8	365.1	515.7	596.6	311.8	498.0	331.2	266.1	379.2	330.3	

OTT Co., Ltd. OTTC-5

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	8	8	8	6	6	6	8	8	6	6	6	8	8	8	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
<b>RATING FACTOR</b>	<b>0.3276</b>	<b>0.4614</b>	<b>0.5326</b>	<b>0.2765</b>	<b>0.4387</b>	<b>0.3739</b>	<b>0.5272</b>	<b>0.609</b>	<b>0.3161</b>	<b>0.5026</b>	<b>0.4292</b>	<b>0.6056</b>	<b>0.6999</b>	<b>0.3634</b>	<b>0.5786</b>	<b>0.4719</b>	<b>0.6661</b>	<b>0.7699</b>	<b>0.4</b>	<b>0.6373</b>	<b>0.546</b>	<b>0.771</b>	<b>0.8914</b>	<b>0.4635</b>	<b>0.7392</b>
OTTC-100S	7.1	10.0	11.5	6.0	9.5	8.1	11.4	13.2	6.8	10.9	9.3	13.1	15.2	7.9	12.5	10.2	14.4	16.7	8.7	13.8	11.8	16.7	19.3	10.0	16.0
OTTC-125S	8.9	12.5	14.4	7.5	11.9	10.1	14.3	16.5	8.6	13.6	11.6	16.4	19.0	9.8	15.7	12.8	18.0	20.9	10.8	17.3	14.8	20.9	24.1	12.6	20.0
OTTC-150S	10.6	15.0	17.3	9.0	14.3	12.2	17.1	19.8	10.3	16.3	13.9	19.7	22.7	11.8	18.8	15.3	21.6	25.0	13.0	20.7	17.7	25.1	29.0	15.1	24.0
OTTC-175S	12.4	17.5	20.2	10.5	16.6	14.2	20.0	23.1	12.0	19.1	16.3	23.0	26.5	13.8	21.9	17.9	25.3	29.2	15.2	24.2	20.7	29.2	33.8	17.6	28.0
OTTC-200S	14.2	20.0	23.1	12.0	19.0	16.2	22.8	26.4	13.7	21.8	18.6	26.2	30.3	15.7	25.1	20.4	28.9	33.4	17.3	27.6	23.7	33.4	38.6	20.1	32.0
OTTC-225S	16.0	22.5	26.0	13.5	21.4	18.2	25.7	29.7	15.4	24.5	20.9	29.5	34.1	17.7	28.2	23.0	32.5	37.5	19.5	31.1	26.6	37.6	43.5	22.6	36.0
OTTC-250S	17.7	25.0	28.8	15.0	23.8	20.3	28.6	33.0	17.1	27.2	23.2	32.8	37.9	19.7	31.3	25.6	36.1	41.7	21.7	34.5	29.6	41.8	48.3	25.1	40.0
OTTC-275S	19.5	27.5	31.7	16.5	26.1	22.3	31.4	36.3	18.8	29.9	25.6	36.1	41.7	21.7	34.5	28.1	39.7	45.9	23.8	38.0	32.5	45.9	53.1	27.6	44.0
OTTC-300S	21.3	30.0	34.6	18.0	28.5	24.3	34.3	39.6	20.5	32.7	27.9	39.4	45.5	23.6	37.6	30.7	43.3	50.0	26.0	41.4	35.5	50.1	57.9	30.1	48.0
OTTC-350S	24.8	35.0	40.4	21.0	33.3	28.4	40.0	46.2	24.0	38.1	32.5	45.9	53.1	27.6	43.9	35.8	50.5	58.4	30.3	48.3	41.4	58.5	67.6	35.1	56.1
OTTC-400S	28.4	40.0	46.2	24.0	38.0	32.4	45.7	52.8	27.4	43.6	37.2	52.5	60.7	31.5	50.1	40.9	57.7	66.7	34.7	55.2	47.3	66.8	77.3	40.2	64.1
OTTC-450S	31.9	45.0	51.9	27.0	42.8	36.5	51.4	59.4	30.8	49.0	41.8	59.0	68.2	35.4	56.4	46.0	64.9	75.1	39.0	62.1	53.2	75.2	86.9	45.2	72.1
OTTC-500S	35.5	50.0	57.7	30.0	47.5	40.5	57.1	66.0	34.2	54.4	46.5	65.6	75.8	39.4	62.7	51.1	72.2	83.4	43.3	69.0	59.2	83.5	96.6	50.2	80.1
OTTC-550S	39.0	55.0	63.5	32.9	52.3	44.6	62.8	72.6	37.7	59.9	51.1	72.2	83.4	43.3	68.9	56.2	79.4	91.7	47.7	75.9	65.1	91.9	106.2	55.2	88.1
OTTC-600S	42.6	60.0	69.2	35.9	57.0	48.6	68.5	79.2	41.1	65.3	55.8	78.7	91.0	47.2	75.2	61.3	86.6	100.1	52.0	82.8	71.0	100.2	115.9	60.3	96.1
OTTC-700S	49.7	70.0	80.8	41.9	66.5	56.7	80.0	92.4	47.9	76.2	65.1	91.8	106.2	55.1	87.8	71.6	101.0	116.8	60.7	96.7	82.8	116.9	135.2	70.3	112.1
OTTC-800S	56.8	80.0	92.3	47.9	76.0	64.8	91.4	105.6	54.8	87.1	74.4	105.0	121.3	63.0	100.3	81.8	115.5	133.4	69.3	110.5	94.6	133.6	154.5	80.3	128.1
OTTC-900S	63.9	90.0	103.9	53.9	85.5	72.9	102.8	118.8	61.6	98.0	83.7	118.1	136.5	70.9	112.8	92.0	129.9	150.1	78.0	124.3	106.5	150.3	173.8	90.4	144.1
OTTC-1000S	71.0	100.0	115.4	59.9	95.1	81.0	114.2	132.0	68.5	108.9	93.0	131.2	151.6	78.7	125.4	102.2	144.3	166.8	86.7	138.1	118.3	167.1	193.1	100.4	160.2
OTTC-1100S	78.1	110.0	126.9	65.9	104.6	89.1	125.6	145.1	75.3	119.8	102.3	144.3	166.8	86.6	137.9	112.5	158.8	183.5	95.3	151.9	130.1	183.8	212.5	110.5	176.2
OTTC-1200S	85.2	120.0	138.5	71.9	114.1	97.2	137.1	158.3	82.2	130.7	111.6	157.5	182.0	94.5	150.4	122.7	173.2	200.2	104.0	165.7	142.0	200.5	231.8	120.5	192.2
OTTC-1250S	88.7	125.0	144.2	74.9	118.8	101.3	142.8	164.9	85.6	136.1	116.2	164.0	189.6	98.4	156.7	127.8	180.4	208.5	108.3	172.6	147.9	208.8	241.4	125.5	200.2
OTTC-1400S	99.4	140.0	161.6	83.9	133.1	113.4	159.9	184.7	95.9	152.5	130.2	183.7	212.3	110.2	175.5	143.1	202.1	233.5	121.3	193.3	165.6	233.9	270.4	140.6	224.2
OTTC-1450S	102.9	145.0	167.3	86.9	137.8	117.5	165.6	191.3	99.3	157.9	134.8	190.3	219.9	114.2	181.8	148.3	209.3	241.9	125.7	200.2	171.5	242.2	280.0	145.6	232.2
OTTC-1500S	106.5	150.0	173.1	89.9	142.6	121.5	171.3	197.9	102.7	163.3	139.5	196.8	227.5	118.1	188.0	153.4	216.5	250.2	130.0	207.1	177.5	250.6	289.7	150.6	240.2
OTTC-1600S	113.6	160.0	184.6	95.9	152.1	129.6	182.8	211.1	109.6	174.2	148.8	209.9	242.6	126.0	200.6	163.6	230.9	266.9	138.7	220.9	189.3	267.3	309.0	160.7	256.3

OTT Co., Ltd. OTTC-S

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	29	29	29	29	29	29	32	32	32	32	32	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.0	44.0	45.0	44.0	47.0	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.0	38.0	39.0	36.0	39.0	27	29.44	32	32
<b>RATING FACTOR</b>	<b>0.6343</b>	<b>0.8959</b>	<b>1.0361</b>	<b>0.5393</b>	<b>0.8607</b>	<b>0.7397</b>	<b>1.0448</b>	<b>1.2085</b>	<b>0.6299</b>	<b>1.0057</b>	<b>0.8211</b>	<b>1.1597</b>	<b>1.3415</b>	<b>0.7</b>	<b>1.1178</b>	<b>0.963</b>	<b>1.36</b>	<b>1.5734</b>	<b>0.8223</b>	<b>1.3135</b>	<b>0.8735</b>	<b>0.7018</b>	<b>1</b>	<b>0.871</b>
OTTC-100S	13.7	19.4	22.4	11.7	18.6	16.0	22.6	26.2	13.6	21.8	17.8	25.1	29.1	15.2	24.2	20.9	29.5	34.1	17.8	28.5	18.9	15.2	21.7	18.9
OTTC-125S	17.2	24.3	28.1	14.6	23.3	20.0	28.3	32.7	17.1	27.2	22.2	31.4	36.3	19.0	30.3	26.1	36.8	42.6	22.3	35.6	23.7	19.0	27.1	23.6
OTTC-150S	20.6	29.1	33.7	17.5	28.0	24.0	34.0	39.3	20.5	32.7	26.7	37.7	43.6	22.8	36.3	31.3	44.2	51.1	26.7	42.7	28.4	22.8	32.5	28.3
OTTC-175S	24.1	34.0	39.3	20.4	32.6	28.0	39.6	45.8	23.9	38.1	31.1	44.0	50.9	26.5	42.4	36.5	51.6	59.7	31.2	49.8	33.1	26.6	37.9	33.0
OTTC-200S	27.5	38.8	44.9	23.4	37.3	32.1	45.3	52.4	27.3	43.6	35.6	50.3	58.1	30.3	48.4	41.7	58.9	68.2	35.6	56.9	37.9	30.4	43.3	37.7
OTTC-225S	30.9	43.7	50.5	26.3	42.0	36.1	50.9	58.9	30.7	49.0	40.0	56.5	65.4	34.1	54.5	46.9	66.3	76.7	40.1	64.0	42.6	34.2	48.8	42.5
OTTC-250S	34.4	48.5	56.1	29.2	46.6	40.1	56.6	65.5	34.1	54.5	44.5	62.8	72.7	37.9	60.5	52.2	73.7	85.2	44.5	71.1	47.3	38.0	54.2	47.2
OTTC-275S	37.8	53.4	61.7	32.1	51.3	44.1	62.3	72.0	37.5	59.9	48.9	69.1	79.9	41.7	66.6	57.4	81.0	93.7	49.0	78.3	52.0	41.8	59.6	51.9
OTTC-300S	41.2	58.2	67.3	35.1	55.9	48.1	67.9	78.6	40.9	65.4	53.4	75.4	87.2	45.5	72.7	62.6	88.4	102.3	53.4	85.4	56.8	45.6	65.0	56.6
OTTC-350S	48.1	67.9	78.6	40.9	65.3	56.1	79.2	91.6	47.8	76.3	62.3	87.9	101.7	53.1	84.8	73.0	103.1	119.3	62.4	99.6	66.2	53.2	75.8	66.1
OTTC-400S	55.0	77.6	89.8	46.7	74.6	64.1	90.5	104.7	54.6	87.2	71.2	100.5	116.3	60.7	96.9	83.5	117.9	136.4	71.3	113.8	75.7	60.8	86.7	75.5
OTTC-450S	61.8	87.4	101.0	52.6	83.9	72.1	101.9	117.8	61.4	98.1	80.1	113.1	130.8	68.3	109.0	93.9	132.6	153.4	80.2	128.1	85.2	68.4	97.5	84.9
OTTC-500S	68.7	97.1	112.2	58.4	93.2	80.1	113.2	130.9	68.2	109.0	89.0	125.6	145.3	75.8	121.1	104.3	147.3	170.5	89.1	142.3	94.6	76.0	108.3	94.4
OTTC-550S	75.6	106.8	123.5	64.3	102.6	88.1	124.5	144.0	75.1	119.8	97.8	138.2	159.9	83.4	133.2	114.8	162.1	187.5	98.0	156.5	104.1	83.6	119.2	103.8
OTTC-600S	82.5	116.5	134.7	70.1	111.9	96.2	135.8	157.1	81.9	130.7	106.7	150.8	174.4	91.0	145.3	125.2	176.8	204.5	106.9	170.8	113.6	91.2	130.0	113.2
OTTC-700S	96.2	135.9	157.1	81.8	130.5	112.2	158.5	183.3	95.5	152.5	124.5	175.9	203.5	106.2	169.5	146.1	206.3	238.6	124.7	199.2	132.5	106.4	151.7	132.1
OTTC-800S	109.9	155.3	179.6	93.5	149.2	128.2	181.1	209.5	109.2	174.3	142.3	201.0	232.5	121.3	193.8	166.9	235.7	272.7	142.5	227.7	151.4	121.6	173.3	151.0
OTTC-900S	123.7	174.7	202.0	105.2	167.8	144.2	203.7	235.7	122.8	196.1	160.1	226.1	261.6	136.5	218.0	187.8	265.2	306.8	160.3	256.1	170.3	136.9	195.0	169.8
OTTC-1000S	137.4	194.1	224.5	116.8	186.5	160.3	226.4	261.8	136.5	217.9	177.9	251.3	290.7	151.7	242.2	208.7	294.7	340.9	178.2	284.6	189.3	152.1	216.7	188.7
OTTC-1100S	151.2	213.5	246.9	128.5	205.1	176.3	249.0	288.0	150.1	239.7	195.7	276.4	319.7	166.8	266.4	229.5	324.1	375.0	196.0	313.1	208.2	167.3	238.3	207.6
OTTC-1200S	164.9	232.9	269.4	140.2	223.8	192.3	271.6	314.2	163.8	261.5	213.5	301.5	348.8	182.0	290.6	250.4	353.6	409.1	213.8	341.5	227.1	182.5	260.0	226.5
OTTC-1250S	171.8	242.6	280.6	146.1	233.1	200.3	283.0	327.3	170.6	272.4	222.4	314.1	363.3	189.6	302.7	260.8	368.3	426.1	222.7	355.7	236.6	190.1	270.8	235.9
OTTC-1400S	192.4	271.8	314.3	163.6	261.1	224.4	316.9	366.6	191.1	305.1	249.1	351.8	406.9	212.3	339.1	292.1	412.5	477.3	249.4	398.4	265.0	212.9	303.3	264.2
OTTC-1450S	199.3	281.5	325.5	169.4	270.4	232.4	328.2	379.7	197.9	316.0	258.0	364.3	421.5	219.9	351.2	302.5	427.3	494.3	258.3	412.7	274.4	220.5	314.2	273.6
OTTC-1500S	206.1	291.2	336.7	175.3	279.7	240.4	339.6	392.8	204.7	326.9	266.9	376.9	436.0	227.5	363.3	313.0	442.0	511.4	267.2	426.9	283.9	228.1	325.0	283.1
OTTC-1600S	219.9	310.6	359.2	187.0	298.4	256.4	362.2	418.9	218.4	348.6	284.6	402.0	465.1	242.7	387.5	333.8	471.5	545.4	285.1	455.3	302.8	243.3	346.7	301.9