

VOFAT MF R0 (2016)

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
MF-1900L in m3/h	28.4	40.0	46.2	24.0	38.0	32.4	45.7	52.8	27.4	43.6	37.2	52.5	60.7	31.5	50.1	40.9	57.7	66.7	34.7	55.2	47.3	66.8	77.2	40.2	64.1
MF-2200L in m3/h	31.9	45.0	51.9	27.0	42.8	36.5	51.4	59.4	30.8	49.0	41.8	59.0	68.2	35.4	56.4	46.0	64.9	75.1	39.0	62.1	53.2	75.2	86.9	45.2	72.1
MF-2400L in m3/h	35.5	50.0	57.7	30.0	47.5	40.5	57.1	66.0	34.2	54.4	46.5	65.6	75.8	39.4	62.7	51.1	72.2	83.4	43.3	69.0	59.1	83.5	96.6	50.2	80.1
MF-2600L in m3/h	44.4	62.5	72.1	37.4	59.4	50.6	71.4	82.5	42.8	68.1	58.1	82.0	94.8	49.2	78.3	63.9	90.2	104.2	54.2	86.3	73.9	104.4	120.7	62.8	100.1
MF-2900C1L in m3/h	53.2	75.0	86.5	44.9	71.3	60.8	85.7	99.0	51.4	81.7	69.7	98.4	113.7	59.0	94.0	76.7	108.2	125.1	65.0	103.6	88.7	125.3	144.8	75.3	120.1
MF-2900C2L in m3/h	62.1	87.5	101.0	52.4	83.2	70.9	99.9	115.4	59.9	95.3	81.4	114.8	132.7	68.9	109.7	89.5	126.3	145.9	75.8	120.8	103.5	146.2	169.0	87.9	140.1
MF-3500C1L in m3/h	71.0	100.0	115.4	59.9	95.0	81.0	114.2	131.9	68.5	108.9	93.0	131.2	151.6	78.7	125.4	102.2	144.3	166.8	86.7	138.1	118.3	167.0	193.1	100.4	160.1
MF-3500C2L in m3/h	88.7	125.0	144.2	74.9	118.8	101.3	142.8	164.9	85.6	136.1	116.2	164.0	189.5	98.4	156.7	127.8	180.4	208.5	108.3	172.6	147.9	208.8	241.4	125.5	200.2

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28
MF-80L in l/s	7.9	11.1	12.8	6.7	10.6	9.0	12.7	14.7	7.6	12.1	10.3	14.6	16.8	8.7	13.9	11.4	16.0	18.5	9.6	15.3	13.1	18.6	21.5	11.2	17.8
MF-2200L in l/s	8.9	12.5	14.4	7.5	11.9	10.1	14.3	16.5	8.6	13.6	11.6	16.4	19.0	9.8	15.7	12.8	18.0	20.8	10.8	17.3	14.8	20.9	24.1	12.6	20.0
MF-2400L in l/s	9.9	13.9	16.0	8.3	13.2	11.3	15.9	18.3	9.5	15.1	12.9	18.2	21.1	10.9	17.4	14.2	20.0	23.2	12.0	19.2	16.4	23.2	26.8	13.9	22.2
MF-2600L in l/s	12.3	17.4	20.0	10.4	16.5	14.1	19.8	22.9	11.9	18.9	16.1	22.8	26.3	13.7	21.8	17.7	25.1	29.0	15.0	24.0	20.5	29.0	33.5	17.4	27.8
MF-2900C1L in l/s	14.8	20.8	24.0	12.5	19.8	16.9	23.8	27.5	14.3	22.7	19.4	27.3	31.6	16.4	26.1	21.3	30.1	34.7	18.1	28.8	24.6	34.8	40.2	20.9	33.4
MF-2900C2L in l/s	17.3	24.3	28.0	14.6	23.1	19.7	27.8	32.1	16.6	26.5	22.6	31.9	36.9	19.1	30.5	24.8	35.1	40.5	21.1	33.6	28.8	40.6	46.9	24.4	38.9
MF-3500C1L in l/s	19.7	27.8	32.1	16.6	26.4	22.5	31.7	36.6	19.0	30.2	25.8	36.4	42.1	21.9	34.8	28.4	40.1	46.3	24.1	38.4	32.9	46.4	53.6	27.9	44.5
MF-3500C2L in l/s	24.6	34.7	40.1	20.8	33.0	28.1	39.7	45.8	23.8	37.8	32.3	45.6	52.6	27.3	43.5	35.5	50.1	57.9	30.1	47.9	41.1	58.0	67.1	34.9	55.6

VOFAT MF R0 (2016)

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
MF-1900L in m3/h	55.0	77.6	89.8	46.7	74.6	64.1	90.5	104.7	54.6	87.2	71.2	100.5	116.3	60.7	96.9	84.4	119.1	137.8	72.0	115.1	75.7	60.8	86.7	75
MF-2200L in m3/h	61.8	87.3	101.0	52.6	83.9	72.1	101.9	117.8	61.4	98.0	80.1	113.1	130.8	68.2	109.0	94.9	134.0	155.1	81.0	129.5	85.2	68.4	97.5	85
MF-2400L in m3/h	68.7	97.0	112.2	58.4	93.2	80.1	113.2	130.9	68.2	108.9	88.9	125.6	145.3	75.8	121.1	105.4	148.9	172.3	90.0	143.8	94.6	76.0	108.3	94
MF-2600L in m3/h	85.9	121.3	140.3	73.0	116.5	100.2	141.5	163.6	85.3	136.2	111.2	157.0	181.6	94.8	151.4	131.8	186.1	215.3	112.6	179.8	118.3	95.0	135.4	118
MF-2900C1L in m3/h	103.1	145.6	168.4	87.6	139.9	120.2	169.8	196.4	102.3	163.4	133.4	188.4	218.0	113.7	181.6	158.2	223.4	258.4	135.1	215.8	141.9	114.0	162.5	142
MF-2900C2L in m3/h	120.2	169.8	196.4	102.2	163.2	140.2	198.1	229.1	119.4	190.6	155.7	219.8	254.3	132.7	211.9	184.5	260.6	301.5	157.6	251.7	165.6	133.0	189.6	165
MF-3500C1L in m3/h	137.4	194.1	224.5	116.8	186.5	160.3	226.4	261.8	136.5	217.9	177.9	251.2	290.6	151.7	242.2	210.9	297.8	344.6	180.1	287.7	189.2	152.0	216.6	189
MF-3500C2L in m3/h	171.8	242.6	280.6	146.0	233.1	200.3	282.9	327.3	170.6	272.4	222.4	314.1	363.3	189.6	302.7	263.6	372.3	430.7	225.1	359.6	236.6	190.1	270.8	236

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
MF-80L in l/s	15.3	21.6	24.9	13.0	20.7	17.8	25.2	29.1	15.2	24.2	19.8	27.9	32.3	16.9	26.9	23.4	33.1	38.3	20.0	32.0	21.0	16.9	24.1	21.0
MF-2200L in l/s	17.2	24.3	28.1	14.6	23.3	20.0	28.3	32.7	17.1	27.2	22.2	31.4	36.3	19.0	30.3	26.4	37.2	43.1	22.5	36.0	23.7	19.0	27.1	23.6
MF-2400L in l/s	19.1	27.0	31.2	16.2	25.9	22.3	31.4	36.4	19.0	30.3	24.7	34.9	40.4	21.1	33.6	29.3	41.4	47.9	25.0	40.0	26.3	21.1	30.1	26.2
MF-2600L in l/s	23.9	33.7	39.0	20.3	32.4	27.8	39.3	45.5	23.7	37.8	30.9	43.6	50.5	26.3	42.0	36.6	51.7	59.8	31.3	49.9	32.9	26.4	37.6	32.8
MF-2900C1L in l/s	28.6	40.4	46.8	24.3	38.8	33.4	47.2	54.5	28.4	45.4	37.1	52.3	60.5	31.6	50.5	43.9	62.0	71.8	37.5	59.9	39.4	31.7	45.1	39.3
MF-2900C2L in l/s	33.4	47.2	54.6	28.4	45.3	39.0	55.0	63.6	33.2	53.0	43.2	61.1	70.6	36.9	58.9	51.3	72.4	83.7	43.8	69.9	46.0	37.0	52.7	45.9
MF-3500C1L in l/s	38.2	53.9	62.4	32.5	51.8	44.5	62.9	72.7	37.9	60.5	49.4	69.8	80.7	42.1	67.3	58.6	82.7	95.7	50.0	79.9	52.6	42.2	60.2	52.4
MF-3500C2L in l/s	47.7	67.4	77.9	40.6	64.7	55.6	78.6	90.9	47.4	75.7	61.8	87.2	100.9	52.7	84.1	73.2	103.4	119.6	62.5	99.9	65.7	52.8	75.2	65.5