

Wanxiang FBH and FBHL R2

Condition Reference #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
Wet Bulb °C	10	10	10	10	10	13	13	13	13	13	16	16	16	16	16	18	18	18	18	18	18	21	21	21	21	21
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	8
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	7
Inlet Water Temperature °C	20	22	23	22	25	23	25	26	25	28	26	28	29	28	31	28	30	31	30	33	31	33	34	33	34	36
Outlet Water Temperature °C	14	16	17	14	17	17	19	20	17	20	20	22	23	20	23	22	24	25	22	25	25	27	28	25	28	28
FBHL-433EP in m3/h	151.2	213.0	245.8	127.6	202.5	172.6	243.3	281.1	145.9	232.0	198.1	279.5	323.0	167.7	267.0	217.8	307.4	355.3	184.6	294.1	252.0	355.8	411.4	213.9	341.2	341.2
FBHL-433EG in m3/h	161.0	226.7	261.7	135.9	215.6	183.7	259.1	299.3	155.3	247.0	210.9	297.6	343.9	178.6	284.3	231.9	327.3	378.3	196.6	313.2	268.3	378.9	438.0	227.8	363.2	363.2
FBHL-433HD in m3/h	149.3	210.3	242.8	126.0	200.0	170.4	240.3	277.6	144.1	229.1	195.6	276.0	319.0	165.6	263.7	215.1	303.6	350.9	182.3	290.5	248.9	351.4	406.3	211.3	336.9	336.9
FBHL-433HL in m3/h	159.9	225.1	259.9	134.9	214.1	182.4	257.2	297.2	154.2	245.2	209.4	295.5	341.5	177.3	282.3	230.3	325.0	375.7	195.2	311.0	266.4	376.2	435.0	226.2	360.7	360.7
FBHL-433HP in m3/h	170.8	240.5	277.6	144.1	228.7	194.9	274.8	317.4	164.8	262.0	223.7	315.7	364.8	189.4	301.6	246.0	347.2	401.3	208.5	332.2	284.6	401.9	464.6	241.6	385.3	385.3
FBHL-433HG in m3/h	182.4	256.9	296.6	154.0	244.3	208.2	293.6	339.1	176.0	279.9	239.0	337.2	389.7	202.4	322.2	262.8	370.9	428.7	222.7	354.9	304.0	429.3	496.4	258.1	411.6	411.6
FBHL-434HD in m3/h	159.9	225.1	259.9	134.9	214.1	182.4	257.2	297.2	154.2	245.2	209.4	295.5	341.5	177.3	282.3	230.3	325.0	375.7	195.2	311.0	266.4	376.2	435.0	226.2	360.7	360.7
FBHL-434HL in m3/h	171.5	241.6	278.8	144.8	229.7	195.8	276.0	318.8	165.5	263.1	224.7	317.1	366.4	190.3	302.9	247.1	348.7	403.1	209.4	333.6	285.9	403.6	466.7	242.7	387.0	387.0
FBHL-434HP in m3/h	180.5	254.3	293.5	152.4	241.8	206.1	290.5	335.6	174.2	277.0	236.5	333.7	385.7	200.3	318.9	260.1	367.1	424.3	220.4	351.2	300.9	424.9	491.2	255.4	407.4	407.4
FBHL-434HG in m3/h	191.8	270.2	311.9	161.9	256.9	218.9	308.7	356.6	185.1	294.3	251.3	354.6	409.8	212.8	338.8	276.3	390.0	450.8	234.2	373.2	319.7	451.4	521.9	271.4	432.8	432.8

Wanxiang FBH and FBHL R2

Condition Reference #	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49
Wet Bulb °C	24	24	24	24	24	27	27	27	27	27	29	29	29	29	29	32.2	32.2	32.2	32.2	32.2	21	25.56	27	28
Range °C	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	6	6	6	8	8	5	5.56	5	5
Approach °C	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	4	6	7	4	7	6	3.89	5	4
Inlet Water Temperature °C	34	36	37	36	39	37	39	40	39	42	39	41	42	41	44	42.2	44.2	45.2	44.2	47.2	32	35.00	37	37
Outlet Water Temperature °C	28	30	31	28	31	31	33	34	31	34	33	35	36	33	36	36.2	38.2	39.2	36.2	39.2	27	29.44	32	32
FBHL-433EP in m3/h	292.8	413.5	478.2	248.9	397.2	341.4	482.2	557.8	290.7	464.2	379.0	535.2	619.2	323.1	515.9	449.3	634.5	734.0	383.7	612.9	403.2	323.9	461.5	402
FBHL-433EG in m3/h	311.7	440.2	509.1	265.0	422.9	363.5	513.4	593.8	309.5	494.2	403.5	569.9	659.2	344.0	549.3	478.3	675.5	781.5	408.5	652.5	429.2	344.9	491.4	428
FBHL-433HD in m3/h	289.1	408.3	472.3	245.8	392.3	337.2	476.2	550.8	287.1	458.4	374.3	528.6	611.5	319.1	509.5	443.7	626.6	724.9	378.9	605.3	398.1	319.9	455.8	397
FBHL-433HL in m3/h	309.5	437.1	505.6	263.1	420.0	360.9	509.8	589.7	307.4	490.7	400.7	565.9	654.6	341.6	545.4	475.0	670.8	776.0	405.6	647.9	426.2	342.4	487.9	425
FBHL-433HP in m3/h	330.6	467.0	540.1	281.1	448.6	385.6	544.6	629.9	328.3	524.2	428.0	604.5	699.2	364.9	582.6	507.4	716.5	829.0	433.3	692.2	455.3	365.8	521.2	454
FBHL-433HG in m3/h	353.2	498.9	576.9	300.3	479.3	411.9	581.8	672.9	350.7	560.0	457.2	645.8	747.0	389.8	622.4	542.0	765.5	885.6	462.9	739.4	486.4	390.8	556.8	485
FBHL-434HD in m3/h	309.5	437.1	505.6	263.1	420.0	360.9	509.8	589.7	307.4	490.7	400.7	565.9	654.6	341.6	545.4	475.0	670.8	776.0	405.6	647.9	426.2	342.4	487.9	425
FBHL-434HL in m3/h	332.1	469.0	542.4	282.3	450.6	387.3	547.0	632.7	329.8	526.5	429.9	607.1	702.3	366.5	585.2	509.6	719.7	832.6	435.2	695.2	457.3	367.4	523.5	456
FBHL-434HP in m3/h	349.6	493.7	571.0	297.2	474.3	407.6	575.8	666.0	347.1	554.2	452.5	639.1	739.3	385.8	616.0	536.4	757.6	876.5	458.1	731.8	481.4	386.8	551.1	480
FBHL-434HG in m3/h	371.4	524.6	606.7	315.8	504.0	433.1	611.8	707.6	368.8	588.9	480.8	679.0	785.5	409.9	654.5	570.0	804.9	931.2	486.8	777.5	511.5	410.9	585.5	510